



# REVALPHA

Double-side coated

Single-side coated

|                                     |     | Adhesion on PET Film (N/20mm)                                    |  |   |  |
|-------------------------------------|-----|--|--|---|--|
|                                     |     | 2.5  | 3.7  | 4.8   | 7.0  |
| Thermal Release Temperature (deg.C) | 90  | No.3198<br>#100<br><br>No.3198LS<br>#100                         | No.3195<br>#100<br><br>No.3196<br>#100,188                       | No.319Y-4L<br>#38,100,188<br><br>No.319Y-4LS<br>#38,100,188 |  |
|                                     | 120 | No.3198M<br>#38,50,100,188<br><br>No.3198MS<br>#25,38,50,100,188 | No.3195M<br>#38,50,100,188<br><br>No.3195MS<br>#25,38,50,100,188 | No.319Y-4M<br>#38,100,188<br><br>No.319Y-4MS<br>#38,100,188 | No.3193M<br>#100<br><br>No.3193MS<br>#50,100 |
|                                     | 150 | No.3198H<br>#100   | No.3195H<br>#100<br><br>No.3195HS<br>#50,100                     | No.319Y-4H<br>#38,100,188<br><br>No.319Y-4HS<br>#38,100,188 |  |
|                                     | 170 |  | No.3195V<br>#38,100,188<br><br>No.3195VS<br>#100                 |   |  |